



**SPECIFICATION :**

**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-ohm Max.
- Rating Current : 1.5A Min.
- Rating Voltage : 120V AC.
- Dielectric Vollage : 1,000 Vrms 60 Sec. Min.

**2. Physical char.**

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.45mm Diamete Phosphor Bronze
- Gold Plating Over Nickel
- Temperature Range : - 40°C /+85°C
- Durability : 500 Mating cycles Min.

**PCB LAYOUT**

<b>Best Connector Enterprise Co.,Ltd</b>		<b>ARTICLE</b>	
<a href="http://www.bce.com.tw">Http://www.bce.com.tw</a>		7118-8P8C-F	

<b>DR.</b>	<b>Housing</b>	<b>Gold Plating</b>	<b>ITEM NO</b>	<b>DWG NO</b>
CHEN HUI	PBT UL94V-0	<input type="checkbox"/> 6U" <input type="checkbox"/> 3U"		EB00140N
<b>CK.D</b>	<b>Color</b>	<input type="checkbox"/> 15U" <input type="checkbox"/> 50U"	<b>TOLERANCE UNLESS</b>	<b>DATE</b>
	BLACK		±0.25mm	06.04.Dec.